



YF-1700UV



- 配置爱普生I3200原装喷头
EPSON I3200 Print head
- LED固化系统,更加节能
LED curing system,more energy-saving
- 进口静音导轨及伺服一体电机
Imported mute rail and servo integrated motor
- 铝合金一体自动清洗墨栈
Big capacity bulk ink system
- 白墨独立搅拌系统
White ink mixing system
- 色彩艳丽,打印画面真实细腻
Bright colors, real and delicate printing pictures

机型/Model		YF-1700			
喷头 Printhead		爱普生I3200		固化系统 Curing System	LED固化系统 LED Water cooling
喷头数量 Print Head number		3		输入格式 File Format	BMP/TIFF/EPS/PDF/AI/JPEG
色彩配置 Print Mode		4C+W+4C	3*4C	RIP软件 RIP	Photoprint/Onyx/Caldera/色彩管理器 Photoprint/Onyx/Caldera/colorget
打印宽幅 Print Width		1520mm		数据传送接口 Data Connector	USB3.0
打印速度 Print Speed (sqm/h)	草图 4pass	16m ² /h	40m ² /h	输入电源 Power	220VAC(±10%)单向, 50/60 HZ 220VAC(±10%) Single Phase, 50/60HZ
	标准 6pass	12m ² /h	35m ² /h	机器功耗 Power Consumption	1800W
	高清 8pass	8m ² /h	25m ² /h	机器尺寸/净重 Machine Size	2.5 m(L)*0.8 m(W)*1.2m(H)
打印分辨率 Print Resolution		720*1800 DPI		包装尺寸 Machine Size	2.6 m(L)*0.7m(W)*0.7m(H)
打印材料 Media Type		超透贴、玻璃贴、车贴、墙布、皮革 transparent stickers, glass stickers Vinly, Wall paper, Leather		环境要求 Environment Requirement	独立、洁净、低尘、少光照、通风良好的 工作间环境温度: 20°C - 25°C, 相对湿度: 50% - 60% seperated, clean, low dust, well-ventilated,environmental temperature:20°C-25°C relative humidity:50%-60%
材料厚度 Media Thickness		材料厚度≤3mm Max. 3mm			
墨水类型 Ink Type		环保UV墨水 UV ink			